

Scissor stair/ attic ladder, type EI-60, fire rated

Certifications:

KOMO:SKG.0372.0457

Fire rating classification: EI-60 according to EN 1634-1

TÜV NORD certified

CodeMark certified for Australia & New Zealand

- Australia CM70087, New Zealand CM70088

Fire rating classification:

EI-60

Casing:

- For structural opening size 700 x 1200 mm
- Height: 250 mm
- Material: wood
- Insulation value cover: $R = 0,5 \text{ m}^2 \cdot \text{K}^\circ / \text{W}$
- The cover will protude 70 mm downwards the ceiling

Ceiling height: mm, (standard up to 3000 mm)
to be specified from top of floor to bottom of cover.

Option:

up to 3500 mm (type Large-H EI-60).

Stairs:



Scissor stair/ attic ladder, type EI-60, fire rated

- Material: aluminium
- Size steps: 360 x 140 x 26 mm
- Adjustable anti-skid steps
- Distance between rungs: 250 mm or more (adjustable)

Projection while opening:

Max. 700 mm at ceiling height 3000 mm (type Large EI-60)

Max. 950 mm at ceiling height 3500 mm (type Large-H EI-60)

Hardware:

- Hook and eye
- Telescopic handrail prepared for padlock to secure retracted stairs
- Stair guide control system

