

# Hoisting hatch, removable roof hatch RHT with flat lids

## Certifications:

KOMO:SKG.0372.0503

## Special size: ..... x ..... mm

- Special sizes are delivered in aluminium

## Product features roof hatch RHT:

- Delivered fully assembled
- Thermally separated and Thermal separated and insulated construction
- Stainless steel egg crate closing system
- Double draftproof and watertight seal between edge and lid
- 4 lifting eyes per lid segment

## Performance:

- Resistance to permanent load (Eurocode EN 1993-1-1) 1050 kg/m<sup>2</sup>
- Insulation value (EN-ISO10077-2):  $U_w \leq 0.276 \text{ W}/(\text{m}^2.\text{K})$
- Sound insulation (EN-ISO 717-1:2013): 26 dB
- Water tightness (EN 12208): Class E 650
- Resistance to wind load (EN 12210): Class E 3000
- Resistance to snow load (EN 1991-1-3): 3,97kN/m<sup>2</sup>
- Impact hard body (EN 356): Class P5A
- Impact soft body (EN 13049): Class 5
- Air permeability (EN 12207): Class 3

## Surface treatment:

Powder coated in RAL 7047 (exterior) and RAL 9010 (interior).



## Hoisting hatch, removable roof hatch RHT with flat lids

### Important:

- Avoid deformation and damage, do not remove lids in strong winds

