

# Roof hatch type RHTD double lid, slope

Special dimensions:..... x ..... mm

- Maximum size: 2500 x 5000 mm
- Special sizes are supplied in aluminium

Product features roof hatch RHTD:

- Delivered fully assembled
- Thermal separated and insulated construction
- Counterbalancing system for assisted opening and controlled closing
- Wind and weather tight sealing
- Lid that engages automatically in open position, with one hand release
- Two point latch for inside operation, with padlock hasps.
- Gorter Handrail on inside lid to safely enter and leave roof hatch
- Option: four powerful motors with closure order control

Performance:

- Resistance to permanent loads (Eurocode EN 1993-1-1): 1050 kg/m<sup>2</sup>
- Sound reduction (EN-ISO140-3): 26 dB
- Watertightness (EN 12208): Class E 650
- Resistance to wind load (EN 12210): Class E 3000
- Resistance to snow loads (EN 1991-1-3): 3.97kN/m<sup>2</sup>
- Impact hard body (EN 356): Class P5A
- Impact soft body (EN 13049): Class 5
- Air permeability (EN 12207): Class 3

Standard coating:

Powder coated in RAL7047 (outside) and RAL9010 (inside).

Attention:



## Roof hatch type RHTD double lid, slope

- Lid is provided with internal stiffeners, small welding spots can show on outside
- To prevent damage and deformation don't open lid with strong winds.

