

Roof hatch RHTG9030 with fixed stair GS50

Roof hatch type RHTG9030

Glazed lid, insulated with HR+++ glass

Standard opening size: 900 x 3000 mm (Hinge side = long side)

Weight: 268 kg

Gorter® - completely assembled with:

- Thermal separated and insulated construction
- Safety glass and burglary resistant
- A diagonal hand rail offers a steady grip when climbing or descending the stairs
- Wind and watertight sealing all around
- 2 powerful electric motors

CodeMark certified for Australia & New Zealand

- Australia CM70087, New Zealand CM70088

Performance according to CE (ETA-18/0831):

- Sound reduction (EN-ISO140-3): 27 dB
- Watertightness (EN 12208): Class E 650
- Resistance to wind load (EN 12210): Class E 2400
- Resistance to snow loads (EN 1991-1-3): 5 kN/m²
- Impact (EN 13049): Class 3
- Air permeability (EN 12207): Class 4

Surface treatment:

Powder coated in RAL 9005/RAL 9010 (outside) and RAL 9010 (inside).



Roof hatch RHTG9030 with fixed stair GS50

Fixed stair, type GS50

Gorter complete assembled. Aluminium, anodized.

Floor height: mm

- Pitch adjustable from 50° - 66°
- Standard room height 2500 mm (50°) - 3000 mm (66°)

Step:

- Size 730 x 175 x 45 mm
- With anti skid profile

Accessories:

- Brackets for fixation on floor and in roof or ceiling opening
- 2 Handrails complete with poles.

IMPORTANT: ready for installation on site

