

Roof hatch RHT7014 and electric scissor stair Large

Certifications:

CE ETA-15/0338

Aboma certificate

TÜV NORD certified according to EN 14975:2010, with label "Baumuster geprüft"

Roof hatch, type RHT7014

Standard opening size: 700 x 1400 mm (Hinge side = long side)

Weight: 68 kg

Product features standard roof hatch RHT:

- Delivered fully assembled
- Thermal separated and insulated construction
- Counter balancing system for assisted opening and controlled closing
- Diagonal handrail in Gorter yellow on the inside of the lid provides extra grip when stepping in and out
- Double sealing for water and weather tightness
- Fully opened lid engages automatically, with release button
- Closure with Gorter hardware and stainless steel Euro cylinder lock, inside and outside operation

Performance according to CE (ETA-15/0338):

- Resistance to permanent loads (Eurocode EN 1993-1-1): 1050 kg/m²
- Insulating (EN-ISO10077-2): $U_w \leq 0.276 \text{ W}/(\text{m}^2\cdot\text{K})$
- Sound reduction (EN-ISO140-3): 26 dB
- Watertightness (EN 12208): Class E 650
- Resistance to wind load (EN 12210): Class E 3000
- Resistance to snow loads (EN 1991-1-3): 3.97kN/m²
- Impact hard body (EN 356): Class P5A



Roof hatch RHT7014 and electric scissor stair Large

- Impact soft body (EN 13049): Class 5
- Air permeability (EN 12207): Class 3

RHT powder coating:

Outside: powder coated in RAL7047

Inside: powder coated in white RAL 9010 (optional black RAL9004)

Electric scissor stair, type Large Gorter

Completely assembled Gorter electric scissor stairs

Casing:

- For structural opening size (W x L x H): 700 x 1200 x 250 mm

Ceiling height: mm, standard 3000 mm.

to be specified from top of floor to bottom of cover.

Stair:

- Material: cast aluminium
- Size steps: 350 x 140 x 32 mm, anti-skid
- Step distance: ca. 250 mm, depending on ceiling height
- Horizontal position of steps is adjustable

Projection while opening:

Max. 700 mm at ceiling height 3000 mm (type Large Gorter)

Max. 950 mm at ceiling height 3500 mm (type Large-H Gorter)

Electric operation:

A powerful motor drives the Gorter electric scissor stairs. The system comes with a control unit



Roof hatch RHT7014 and electric scissor stair Large

and a wireless RF remote control as standard.

Hardware:

- Compact control unit 230V AC, motor (24V DC)
- Wireless RF remote control
- Stair guide control system

