

# Roof hatch glazed RHTG1015

## Certifications:

CE ETA-18/0831

## **Roof hatch type RHTG1015**

*Glazed lid, insulated with HR+++ glass*

Standard clearance: 1000 x 1500 mm (Hinge side = long side)

Weight: 163 kg

## Gorter® completely assembled with:

- Thermal separated and insulated construction
- Safety glass and burglary resistant
- A diagonal hand rail offers a steady grip when climbing or descending the stairs
- Wind and watertight sealing all around
- 2 powerful electric motors

## Performance according to CE (ETA-18/0831):

- Insulating value HR+++ glass:  $U \leq 0.500 \text{ W}/(\text{m}^2.\text{K})$
- Insulating (EN-ISO10077-2):  $U_w \leq 0.83 \text{ W}/(\text{m}^2.\text{K})$
- Sound reduction (EN-ISO140-3): 27 dB
- Watertightness (EN 12208): Class E 650
- Resistance to wind load (EN 12210): Class E 2400
- Resistance to snow loads (EN 1991-1-3): 5 kN/m<sup>2</sup>
- Impact (EN 13049): Class 3
- Air permeability (EN 12207): Class 4

## Surface treatment:



## Roof hatch glazed RHTG1015

Powder coated in RAL9005/RAL9010 (outside) and RAL9010 (inside).

*We do not recommend the combination with an attic ladder or scissor stairs!*



**Gorter**<sup>®</sup>

© Gorter Group™