

Roof hatch RHTG1015 with fixed stair GS50

Certifications:

CE ETA-18/0831

Aboma certificate

Roof hatch type RHTG1015

Glazed lid, insulated with HR+++ glass

Standard opening size: 1000 x 1500 mm (Hinge side = long side)

Weight: 163 kg

Gorter® - completely assembled with:

- Thermal separated and insulated construction
- Safety glass and burglary resistant
- A diagonal hand rail offers a steady grip when climbing or descending the stairs
- Wind and watertight sealing all around
- 2 powerful electric motors

Performance according to CE (ETA-18/0831):

- Insulating value HR+++ glass: $U \leq 0.500 \text{ W/(m}^2\cdot\text{K)}$
- Insulating (EN-ISO10077-2): $U_w \leq 0.83 \text{ W/(m}^2\cdot\text{K)}$
- Sound reduction (EN-ISO140-3): 27 dB
- Watertightness (EN 12208): Class E 650
- Resistance to wind load (EN 12210): Class E 2400
- Resistance to snow loads (EN 1991-1-3): 5 kN/m^2
- Impact (EN 13049): Class 3
- Air permeability (EN 12207): Class 4

Surface treatment:

Roof hatch RHTG1015 with fixed stair GS50

Powder coated in RAL9005/RAL9010 (outside) and RAL9010 (inside).

Fixed stair, type GS50

Gortor complete assembled. Aluminium, anodized.

Floor height: mm

- Pitch adjustable from 50° - 66°
- Standard room height 2500 mm (50°) - 3000 mm (66°)

Step:

- Size 730 x 175 x 45 mm
- With anti skid profile

Accessories:

- Brackets for fixation on floor and in roof or ceiling opening
- 2 Handrails complete with poles.

IMPORTANT: ready for installation on site

