

# Roof hatch glazed RHTG

## Certifications:

*CE ETA-18/0831*

## **Roof hatch type RHTG**

*Glazed lid, insulated with HR+++ glass*

## Opening (mm) - Weight:

- RHTG1015: 1000 x 1500 mm / 173 kg
- RHTG1020: 1000 x 2000 mm / 219 kg
- RHTG1025: 1000 x 2500 mm / 264 kg
- RHTG1030: 1000 x 3000 mm / 309 kg

*Hinge side = long side*

## Product features roof hatch RHTG:

- Delivered fully assembled
- Lid with HR+++ glass
- Thermal separated and insulated construction
- Safety glass and burglary resistant
- A diagonal Gorter hand rail offers a steady grip when climbing or descending the stairs
- Wind and watertight sealing all around
- 2 powerful electric motors

## Performance according to CE (ETA-18/0831):



## Roof hatch glazed RHTG

- Insulating value HR+++ glass:  $U \leq 0.500 \text{ W}/(\text{m}^2.\text{K})$
- Insulating (EN-ISO10077-2):  $U_w \leq 0.83 \text{ W}/(\text{m}^2.\text{K})$
  
- Sound reduction (EN-ISO140-3): 27 dB
  
- Watertightness (EN 12208): Class E 650
- Resistance to wind load (EN 12210): Class E 2400
- Resistance to snow loads (EN 1991-1-3):  $5 \text{ kN}/\text{m}^2$
- Impact (EN 13049): Class 3
- Air permeability (EN 12207): Class 4

### Surface treatment:

Powder coated in RAL9005/RAL9010 (outside) and RAL9010 (inside).

*We do not recommend the combination with an attic ladder or scissor stairs!*