

# Roof hatch RHT7014 and electric scissor stair Large

## Certifications:

CE ETA-15/0338

Aboma certificate

TÜV NORD certified according to EN 14975:2010, with label "Baumuster geprüft"

## **Roof hatch, type RHT7014**

Standard opening size: 700 x 1400 mm (Hinge side = long side)

Weight: 68 kg

## Gorter® - completely assembled with:

- Thermal separated and insulated construction
- Counter balancing system for assisted opening and controlled closing
- Diagonal hand rail to safely enter and leave roof hatch
- Double sealing for water and weather tightness
- Fully opened lid engages automatically, with release button
- Stainless steel Eurocylinder lock, in- and outside operation

## Performance according to CE (ETA-15/0338):

- Resistance to permanent loads (Eurocode EN 1993-1-1): 1050 kg/m<sup>2</sup>
- Insulating (EN-ISO10077-2):  $U_w \leq 0.32 \text{ W}/(\text{m}^2 \cdot \text{K})$
- Sound reduction (EN-ISO140-3): 26 dB
- Watertightness (EN 12208): Class E 650
- Resistance to wind load (EN 12210): Class E 3000
- Resistance to snow loads (EN 1991-1-3): 3.97kN/m<sup>2</sup>
- Impact hard body (EN 356): Class P5A
- Impact soft body (EN 13049): Class 5
- Air permeability (EN 12207): Class 3



# Roof hatch RHT7014 and electric scissor stair Large

## RHT powder coating:

Outside: powder coated in RAL7047

Inside: powder coated in white RAL 9010 (optional black RAL9004)

## **Electric scissor stair, type Large**

Completely assembled Gorter electric scissor stairs

## Casing:

- For structural opening size (W x L x H): 700 x 1200 x 250 mm

Ceiling height: ..... mm, standard 3000 mm.  
to be specified from top of floor to bottom of cover.

## Stair:

- Material: cast aluminium
- Size steps: 350 x 140 x 32 mm, anti-skid
- Step distance: ca. 250 mm, depending on ceiling height
- Horizontal position of steps is adjustable

## Projection while opening:

Max. 700 mm at ceiling height 3000 mm (type Large)

Max. 950 mm at ceiling height 3500 mm (type Large-H)

## Electric operation:

A powerful motor drives the Gorter electric scissor stairs. The system comes with a control unit and a wireless RF remote control as standard.

## Hardware:



## Roof hatch RHT7014 and electric scissor stair Large

- Compact control unit 230V AC, motor (24V DC)
- Wireless RF remote control
- Stair guide control system

