

# Roof hatch RHTG with fixed stair GS55

## Certifications:

*CE ETA-18/0831*

*Aboma certificate*

## **Roof hatch type RHTG**

*Glazed lid, insulated with HR+++ glass*

## Opening (mm) - Weight:

- RHTG1020: 1000 x 2000 mm / 219 kg
- RHTG1025: 1000 x 2500 mm / 264 kg
- RHTG1030: 1000 x 3000 mm / 309 kg

*Hinge side = long side*

## Product features roof hatch RHTG:

- Delivered fully assembled
- Lid with HR+++ glass
- Thermal separated and insulated construction
- Safety glass and burglary resistant
- A diagonal Gorter handrail offers a steady grip when climbing or descending the stairs
- Wind and watertight sealing all around
- 2 powerful electric motors

## Performance according to CE (ETA-18/0831)



## Roof hatch RHTG with fixed stair GS55

- Insulating value Gorter HR+++ glass:  $U \leq 0.500 \text{ W}/(\text{m}^2.\text{K})$
- Insulating (EN-ISO10077-2):  $U_w \leq 0.83 \text{ W}/(\text{m}^2.\text{K})$
  
- Sound reduction (EN-ISO140-3): 27 dB
  
- Watertightness (EN 12208): Class E 650
- Resistance to wind load (EN 12210): Class E 2400
- Resistance to snow loads (EN 1991-1-3):  $5 \text{ kN}/\text{m}^2$
- Impact (EN 13049): Class 3
- Air permeability (EN 12207): Class 4

### Surface treatment:

Powder coated in RAL 9005/RAL 9010 (outside) and RAL 9010 (inside).

### **Fixed stair, type GS55 Gorter**

Gorter complete assembled. Aluminium, anodized.

### Floor height: ..... mm

- Pitch adjustable from  $55^\circ$  -  $65^\circ$
- Standard room height 3000 mm ( $55^\circ$ ) - 3370 mm ( $65^\circ$ )

### Step:

- Size 730 x 175 x 45 mm
- With anti skid profile

### Accessories

- Brackets for fixation on floor and in roof or ceiling opening
- 2 Handrails complete with poles.



# Roof hatch RHTG with fixed stair GS55

*IMPORTANT: ready for installation on site*

